

High quality adhesive for fast and powerful bonding

Description

High quality pasty adhesive in a solvent solution. MONTAGE-S is based on caoutchouc and synthetic resins. It is used for fast and powerful bonding on almost all construction materials. No need for drilling, screwing or nailing.

Fields of application

MONTAGE-S is suitable for direct bonding on almost all kinds of substrates, like wood frames and skirting boards, panels, wood floorings, wood and metallic baseboards, ceramic tiles, decorative frames, natural stones, wall sockets etc.

MONTAGE-S is not suitable for bonding mirrors, polystyrene insulation boards or other materials sensitive to solvents.

Technical data

Color:	beige
Solid material content:	approximately 72%
Density:	1,2 kg/lit
Temperature of application:	from +5°C up to +40°C
Temperature resistance:	from -20°C up to +50°C
Detachment strength (MEL 050):	
• after 24 hours:	> 1,5 N/mm ²
• after 72 hours:	> 2 N/mm ²
• after 7 days:	> 2 N/mm ²

Directions for use

1. Substrate

Substrates must be dry and free from dust, grease, etc.

2. Application

MONTAGE-S is ready-to-use. The cartridge is inserted in the special hand gun and the nozzle is cut slantwise.

For bonding light weight materials

MONTAGE-S is applied on one surface in spots in a distance of 20 cm between them or strips. Then the surfaces are assembled by pressing down firmly or by using a rubber hammer.

For bonding heavy weight materials or materials subject to pressure, MONTAGE-S is initially applied as mentioned above by putting both surfaces in contact with one another. Then they must be separated and wait for 5 minutes before readjusting the assembly by pressing down firmly or by using a rubber hammer. Heavy weight materials exceeding 10 kg/m² must be supported for 8-24 hours

Cleaning:

While fresh the adhesive can be washed away with water. Once it has hardened it can be removed only mechanically.

Consumption

Typical consumption: 1 cartridge / 12 linear meters.

Packaging

Cartridge 310 ml.

MONTAGE-S



Shelf-life - Storage

Shelf-life is 12 months, in dry and not high temperature conditions.

Remarks

- Materials bonded with MONTAGE-S can receive loading after 48 hours.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:
17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475
www.isomat.net e-mail: info@isomat.net

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product.

