



Cosmos Lac AE

1 Pindou str.
17672 Kallithea, Athens, Greece.
Tel.: +30 2109570222 -
Fax: +30 2109566671
factory@cosmoslac.com
www.cosmoslac.com

Technical Data Sheet

PRODUCT	COSMOS LAC SPRAY SILICON LUBE 203
DESCRIPTION/USES	Silicon lube is a high quality multi-purpose mechanical lubricant. Excellent water repellence; ideal for all general and light duty mechanical lubrication purposes Provides long term lubrication any metallic or plastic part.
Viscosity	18-25 sec (Flow Cup DIN4, 20°C)
Density	0.8-0.9 g/L (Density Cup 100cm ³ /20°C, ASTM D – 1475)
VOC content	600 g/L
Flash Point	-104 °C (based on propellant)
Drying time	Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).
Color	Transparent
Can Pressure	4bar (20 °C) , 8 bar (50 °C)
Contents	400ml
Application	Remove all dust, rust and oil from the surface. Protect the area which you don't want to be sprayed. Shake the can thoroughly and spray at a distance of 10cm from the surface. Try the spray on testing surface .Apply the silicone spray in a thin layer. . Best application temperature : 20 °C - 25 °C
After use	Spray holding the can inverted for 3". Clean the caps with solvent.
Storage	5-35°C. Do not put in vehicles.

ISSUED 27 November 2017, factory@cosmoslac.com