



Cosmos Lac AE

1 Pindou str.
 17672 Kallithea, Athens, Greece.
 Tel.: +30 2109570222 -
 Fax: +30 2109566671
 factory@cosmoslac.com
 www.cosmoslac.com

Technical Data Sheet

PRODUCT	COSMOS LAC PENETRATING OIL SPRAY 208
DESCRIPTION/USES	Synthetic base lubricant. Lubricates perfectly and fast all metals and contributes to efficient operation. Eliminates corrosion by penetrating and freeing metal rusted parts. Protects against corrosion. A thin layer will ensure rust free tools, metal parts etc. Ignites damp engines for trouble free starting, starting on to plugs, plug leads distributor leads
Viscosity	18-25 sec (Flow Cup DIN4, 20°C)
Density	0.8-0.9 g/L (Density Cup 100cm ³ /20°C, ASTM D – 1475)
VOC content	490 g/L
Flash Point	-104 °C (based on propellant)
Drying time	Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).
Color	Transparent
Can Pressure	4bar (20 °C) , 8 bar (50 °C)
Contents	400ml
Application	Protect the area which you don't want to be sprayed. Shake the can thoroughly and spray at a distance of 10cm from the surface. Best application temperature : 20 °C - 25 °C
After use	Spray holding the can inverted for 3". Clean the caps with solvent.
Storage	5-35°C. Do not put in vehicles.

ISSUED 27 November 2017, factory@cosmoslac.com