

DECOFIX	Technical Data Sheet (TDS) Declaration of Performance № 2260	COD: CC-PF-001
		EDITIA: 1
		REVIZIA: 0
		DATA: 15.01.2020.

1 DATE : 09.08.2020.
2 Product Name: Fiberglass mesh 110gr 10x10mm
3 Production Date: 23.11.2020.
4 Storage Term: 2 years after date of production in dry Warehouse

№	Indicator	Measure	Norm	Test result	Test Method
1	Number of threads 10 cm (warp)	H/10 cm y/10 cm	9-12	11	EAD 040016-00-0404:2016, Cl. 2.2.6
2	Number of threads 10 cm (weft)	H/10 cm y/10 cm	9-12	11	EAD 040016-00-0404:2016, Cl. 2.2.6
3	Width	cm/cm	99,5-101	99,9	EAD 040016-00-0404:2016, Cl. 2.2.5
4	Mass per unit	g/m ² gr/m ²	105-115	108	EAD 040016-00-0404:2016, Cl. 2.2.8
5	Ash content	%	not less than 8	23,8	EAD 040016-00-0404:2016, Cl. 2.2.2
6	Tearing Force (warp)	H/5 cm N/5 cm	not less than 1200	1 350	u\o 040016-00-0404:2016, Cl. 2.2.7
7	Tearing Force (weft)	H/5 cm N/5 cm	not less than 1200	1 554	u\o 040016-00-0404:2016, Cl. 2.2.7
8	Tearing Force after 28 days storage (warp)	H/50 mm N/50 mm	not less than 600	750	u\o 040016-00-0404:2016, Cl. 2.2.7
9	Tearing Force after 28 days storage (weft)	H/50 mm N/50 mm	not less than 900	1 110	u\o 040016-00-0404:2016, Cl. 2.2.7
10	Cell size warp direction	mm/mm	not less than 10	10,0	EAD 040016-00-0404:2016, Cl. 2.2.4
11	Cell size weft direction	mm/mm	not less than 10	10,0	EAD 040016-00-0404:2016, Cl. 2.2.4

Production Director

